

WRINKLE

Paint spray

Art. 767 / 9 / 0423


VFL
Vismara Farbladen



Properties	WRINKLE coatings result in very resistant, scratch-resistant and effective wrinkle varnish surfaces. The resistance to acids, petrol, solvents etc. is excellent.
Field of application	Suitable for motor vehicles, equipment, mechanical engineering, decoration, etc.
Pretreatment	The surfaces to be painted must be clean, dry, free of rust, oil, grease and wax. Carefully cover areas not to be sprayed.
Processing	<p>WRINKLE is applied directly without primer. Avoid sun and wind. Shake the can before use until the balls move audibly for about 20 seconds. Shake well even when working in between. Spray distance 25–30cm.</p> <p>Apply WRINKLE paint spray as evenly as possible in 2–4 layers. Spray thin layers in the cloister. Wait a few minutes after each shift, but no longer than 10 minutes. After use, invert can and operate valve until only gas escapes. The coating thickness determines the shrinkage size.</p>
Drying	The shrinking effect and the surface hardness is increased by forced drying with a baking cabin, heating lamp, infrared lamps, oven or hairdryer. Baking temperature: 80–30–50 °C. Baking time: 1,5–3 hours
Extensiveness	0,5–1 m ² , depending on the quantity applied and the condition of the substrate.
Delivery form	Aerosol cans of 400ml.
Shelf life	WRINKLE can be stored for at least 24 months in the well closed original container.
Gloss level	Silk matt
Colours	No. 217 black
Registration	CPID 623125
Classification	For information on chemical properties and hazards as well as regulations regarding transport, processing, storage, disposal, etc., please refer to the safety data sheet.
Note	<p>This leaflet is only intended as a reference and non-binding advice. The processing must be adapted to the corresponding conditions. In special cases we recommend to contact our technical service. However, all data and information on the suitability and application of the delivered products do not exempt the processor from carrying out his own tests and trials. A claim for damages for omitted, incomplete or incorrect information is excluded. This applies in particular also if other products are used in the paint build-up system.</p> <p>Furthermore, we refer to our General Terms and Conditions (GTC) on our homepage.</p>



Farben



Knuchel

High quality - Top finish